

# Install Nginx Webserver on Linux Ubuntu Server 20.04 LTS

```
$ sudo apt update
$ sudo apt upgrade
```

Stop apache2 if that webserver is also installed and running.

```
sudo systemctl stop apache2.service
```

## Installing Nginx Server

```
$ sudo apt install nginx
```

After the installation is completed, start the Nginx service and enable it to launch every time at system boot. Check the status of Nginx.

```
sudo systemctl start nginx
sudo systemctl enable nginx
sudo systemctl status nginx
```

## NGinx Could not Bind to http port 80 because Apache is already Bind to that Port

```
Jun 10 02:33:16 xsvr nginx[77940]: nginx: [emerg] bind() to 0.0.0.0:80 failed (98: Address already in use)
```

```
Jun 10 02:33:16 xsvr nginx[77940]: nginx: [emerg] bind() to :::80 failed (98: Address already in use)
```

```
Jun 10 02:33:17 xsvr nginx[77940]: nginx: [emerg] bind() to 0.0.0.0:80 failed (98: Address already in use)
```

```
Jun 10 02:33:17 xsvr nginx[77940]: nginx: [emerg] bind() to :::80 failed (98: Address already in use)
```

```
Jun 10 02:33:17 xsvr nginx[77940]: nginx: [emerg] bind() to 0.0.0.0:80 failed (98: Address already in use)
```

```
Jun 10 02:33:17 xsvr nginx[77940]: nginx: [emerg] bind() to :::80 failed (98: Address already in use)
```

```
Jun 10 02:33:18 xsvr nginx[77940]: nginx: [emerg] still could not bind() Jun 10 02:33:18 xsvr
```

```
systemd[1]: nginx.service: Control process exited, code=exited, status=1/FAILURE
```

```
Jun 10 02:33:18 xsrv systemd[1]: nginx.service: Failed with result 'exit-code'.
```

```
Jun 10 02:33:18 xsrv systemd[1]: Failed to start A high performance web server and a reverse proxy server.
```

## Change Apache2 Default Port to Custom Port on Ubuntu / Debian

Change Apache port on Debian/Ubuntu. Edit /etc/apache2/ports.conf file, \$ sudo vi /etc/apache2/ports.conf. Find the following line: Listen 80. ..

```
sudo vim /etc/apache2/ports.conf
```

Find the following line:

```
Listen 80
```

Change it to a random port of you choice, for example 8090.

```
Listen 8090
```

This entry make the server to accept connections on port 8090 on all interfaces. To make the server accept connections on port 8090 for a specific interface, just include the corresponding network interface's IP address as shown below.

```
Listen 192.168.1.101:8090
```

This will be helpful if your server has multiple IP addresses or network interfaces.

Save and close the file.

If the ports.conf file also has the following, may need to change ssl port 443 to port 444 or something else.

```
<IfModule ssl_module>
    Listen 443
</IfModule>

<IfModule mod_gnutls.c>
    Listen 443
</IfModule>
```

Additionally, in Ubuntu and Debian, you also have to change the port number in /etc/apache2/sites-enabled/000-default.conf file too.

```
$ sudo vi /etc/apache2/sites-enabled/000-default.conf
```

Find the following line and change the port number.

```
<VirtualHost *:8090>
```

Save and close the file.

Then, restart Apache service to take effect the changes.

```
$ sudo systemctl restart apache2
```

Now let us verify the port settings:

```
$ sudo netstat -tulpn | grep :8090
```

Sample Output:

```
tcp6      0      0 :::880      :::*      LISTEN      4066/apache2
```

From:

<https://installconfig.com/> - Install Config Wiki

Permanent link:

[https://installconfig.com/doku.php?id=install\\_nqinx\\_webserver\\_linux\\_ubuntu\\_server\\_20\\_04\\_lts&rev=1591758332](https://installconfig.com/doku.php?id=install_nqinx_webserver_linux_ubuntu_server_20_04_lts&rev=1591758332)

Last update: 2020/06/10 03:05

